



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: E21B 19/16, E21B 19/06	A1	(11) International Publication Number: WO 00/11309 (43) International Publication Date: 02 March 2000 (02.03.2000)
(21) International Application Number: PCT/GB99/02704 (22) International Filing Date: 16 August 1999 (16.08.1999) (30) Priority Data: 9818366.8 24 August 1998 (24.08.1998) GB (60) Parent Application or Grant WEATHERFORD/LAMB, INC. [/]; (). HARDING, Richard, Patrick [/]; (). PIETRAS, Bernd-Georg [/]; (). PIETRAS, Bernd-Georg [/]; (). LIND, Robert; ().	Published	
(54) Title: METHOD AND APPARATUS FOR CONNECTING TUBULARS USING A TOP DRIVE (54) Titre: PROCEDE ET APPAREIL DE RACCORDEMENT DE TUBAGES UTILISANT UNE COMMANDE SUPERIEURE		
(57) Abstract <p>An apparatus for facilitating the connection of tubulars, said apparatus comprising a winch (15), at least one wire line (4, 5) and a device (2) for gripping a tubular (3), the arrangement being such that, in use, the winch (15) can be used to winch said at least one wire (4, 5) and said device (2) to position a tubular (3) below said top drive.</p> (57) Abrégé <p>La présente invention concerne un appareil permettant de raccorder des tubages, comprenant un treuil (15), au moins une ligne de câble (4, 5) et un dispositif (2) de préhension de tube (3). Cette disposition est telle, que lors de son utilisation, le treuil (15) peut être utilisé pour le treuillage du câble (4, 5) et du dispositif (2) précités de manière à placer le tubage (3) sous la commande supérieure.</p>		

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : E21B 19/16, 19/06		A1	(11) International Publication Number: WO 00/11309
			(43) International Publication Date: 2 March 2000 (02.03.00)
(21) International Application Number: PCT/GB99/02704		(81) Designated States: AU, CA, GB, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 16 August 1999 (16.08.99)			
(30) Priority Data: 9818366.8 24 August 1998 (24.08.98) GB		Published With international search report.	
(71) Applicant (for all designated States except US): WEATHER-FORD/LAMB, INC. [US/US]; CSC - The United States Corporation Company, 1013 Centre Road, Wilmington, DE 19805 (US).			
(71) Applicant (for GB only): HARDING, Richard, Patrick [GB/GB]; Marks & Clerk, 4220 Nash Court, Oxford Business Park South, Oxford OX4 2RU (GB).			
(72) Inventor; and (75) Inventor/Applicant (for US only): PIETRAS, Bernd-Georg [DE/DE]; Sandriedeweg 12, D-30900 Wedemark (DE).			
(74) Agent: LIND, Robert; Marks & Clerk, 4220 Nash Court, Oxford Business Park South, Oxford OX4 2RU (GB).			

(54) Title: METHOD AND APPARATUS FOR CONNECTING TUBULARS USING A TOP DRIVE

(57) Abstract

An apparatus for facilitating the connection of tubulars, said apparatus comprising a winch (15), at least one wire line (4, 5) and a device (2) for gripping a tubular (3), the arrangement being such that, in use, the winch (15) can be used to winch said at least one wire (4, 5) and said device (2) to position a tubular (3) below said top drive.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CJ	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Description

5

10

15

20

25

30

35

40

45

50

55

5
METHOD AND APPARATUS FOR CONNECTING TUBULARS USING A TOP
DRIVE

10
This invention relates to a method and apparatus for facilitating the connection of
15 5 tubulars using a top drive and is, more particularly but not exclusively, for facilitating
the connection of a section or stand of casing to a string or casing.

20
In the construction of wells such as oil or gas wells, it is usually necessary to
line predrilled holes with a string of tubulars known as casing. Because of the size of
the casing required, sections or stands of say two sections of casing are connected to
25 10 each other as they are lowered into the well from a platform. The first section or stand
of casing is lowered into the well and is usually restrained from falling into the well by
a spider located in the platform's floor. Subsequent sections or stands of casing are
moved from a rack to the well centre above the spider. The threaded pin of the section
30 or stand of casing to be connected is located over the threaded box of the casing in the
15 well to form a string of casing. The connection is made-up by rotation therebetween.

35
It is common practice to use a power tong to torque the connection up to a
predetermined torque in order to perfect the connection. The power tong is located on
the platform, either on rails, or hung from a derrick on a chain. However, it has recently
40 been proposed to use a top drive for making such connection.

20
Prior to the present invention, pipe handling devices moved pipes to be
45 connected to a tubular string from a rack to the well centre using articulated arms or,
more commonly, a pipe elevator suspended from the drilling tower.

The present invention provides an alternative to these devices.

50

Accordingly, a first aspect of the present invention provides an apparatus for facilitating the connection of tubulars, said apparatus comprising a winch, at least one wire line and a device for gripping a tubular the arrangement being such that, in use, the winch can be used to winch said at least one wire and said device to position a tubular below said top drive.

Further features are set out in Claims 2 to 6.

According to a second aspect of the present invention there is provided a method of facilitating the connection of tubulars using a top drive and comprising the steps of attaching at least one wire to a tubular, the wire depending from the top drive or from a component attached thereto, and winching the wire and the tubular upwards to a position beneath the top drive.

According to a third aspect of the present invention there is provided an apparatus for facilitating the connection of tubulars using a top drive, said apparatus comprising an elevator and a pair of bails, characterised in that said elevator is, in use, movable in relation to said pair of bails.

According to a fourth aspect of the present invention there is provided an apparatus for facilitating the connection of tubulars using a top drive, said apparatus comprising an elevator (102) and a pair of bails (103, 104), characterised in that said elevator (102) is, in use, movable relative to said pair of bails (103, 104).

For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the accompanying drawings in which:

Figures 1a to 1g are perspective views of an apparatus in accordance with a first embodiment of the present invention at various stages of operation; and

Figures 2a to 2d are perspective views of an apparatus in accordance with a second embodiment of the invention at various stages of operation.

Referring to Figures 1a to 1e there is shown an apparatus which is generally identified by reference numeral 1.

The apparatus 1 comprises a clamp 2 for retaining a tubular 3. The clamp 2 is suspended on wires 4, 5 which are connected thereto on opposing sides thereof. The wire 5 passes through an eye 6 in lug 7 which is attached to a spherical bearing in arm 8 of a suspension unit 9 at the point at which the arm 8 is connected to a hydraulic motor 10. The wire is connected to the hydraulic motor 10 in a corresponding manner. The suspension unit 9 is of a type which enables displacement of the tubular 3 when connected to a tool 17 (see below), relative to a top drive 13, along a number of different axes. The wires 4, 5 pass across the suspension unit 9 and over pulley wheels 11 which are rotatably arranged on a plate 12. The plate 12 is fixed in relation to a top drive generally identified by reference numeral 13. The wires 4, 5 then pass over drums 14 to which the wires 4, 5 are also connected. The drums 14 are rotatable via a hydraulic winch motor 15.

In use, the clamp 2 is placed around a tubular below a box 16 thereof. The hydraulic winch motor 15 is then activated, which lifts the tubular 3 (conveniently from a rack) and towards a tool 17 for gripping the tubular 3 (Fig. 1b). The tubular 3 encompasses the tool 17 at which point the hydraulic winch motor 15 is deactivated (Fig. 1c). During this operation the elevator 18 is held away from the tool 17 by piston and cylinders 19, 20 acting on bails 21 and 22. The suspension unit 9 allows the hydraulic motor 10 and the arrangement depending therebelow to move in vertical and horizontal planes relative to the top drive 13. The eyes 6 in lugs 7 maintain the wires 4

5 and 5 in line with the tubular 3 during any such movement. The tool 17 may now be
used to connect the tubular to the tubular string. More particularly, the tool may be of a
10 type which is inserted into the upper end of the tubular, with gripping elements of the
tool being radially displaceable for engagement with the inner wall of the tubular so as
15 to secure the tubular to the tool. Once the tool is secured to the tubular, the hydraulic
motor 10 is activated which rotates the tool 17 and hence the tubular 3 for engagement
with a tubular string held in a spider.

20 The clamp 2 is now released from the tubular 3, and the top drive 13 and hence
apparatus 1 is now lifted clear of the tubular 3. The elevator 18 is now swung in line
10 with the apparatus 1 by actuation of the piston and cylinders 19 and 20 (Fig. 1d).

25 The top drive 13 is then lowered, lowering the elevator 18 over the box 16 of the
tubular 3. The slips in the elevator 18 are then set to take the weight of the entire
tubular string. The top drive is then raised slightly to enable the slips in the spider to be
30 released and the top drive is then lowered to introduce the tubular string into the
15 borehole.

35 Referring to Figures 2a to 2d there is shown an apparatus which is generally
identified by reference numeral 101.

40 The apparatus 101 comprises an elevator 102 arranged at one end of bails 103,
104. The bails 103, 104 are movably attached to a top drive 105 via axles 106 which
20 are located in eyes 107 in the other end of the bails 103, 104. Piston and cylinders 108,
109 are arranged between the top drive 105 and the bails. One end of the piston and
45 cylinders 108, 109 are movably arranged on axles 110 on the top drive. The other end
of the piston and cylinders 108, 109 are movably arranged on axles 111, 112 which are
50

located in lugs 113, 114 located approximately one-third along the length of the bails 103, 109.

The elevator 102 is provided with pins 115 on either side thereof and projecting therefrom. The pins 115 are located in slots 116 and 116a. A piston 117, 118 and cylinder 119, 120 are arranged in each of the bails 103, 104. The cylinders are arranged in slot 121, 122. The piston 117, 118 are connected at their ends to the pins 115. The cylinders 119, 120 are prevented from moving along the bails 103, 104 by cross members 123 and 124. A hole is provided in each of the cross members to allow the pistons to move therethrough.

In use, a tubular 125 is angled from a rack near to the well centre. The tubular may however remain upright in the rack. The clamp 102 is placed around the tubular below a box 126 (Figure 2a). The top drive is raised on a track on a derrick. The tubular is lifted from the rack and the tubular swings to hang vertically (Figure 2b). The piston and cylinders 108, 109 are actuated, extending the pistons allowing the bails 103, 104 to move to a vertical position. The tubular 125 is now directly beneath a tool 127 for internally gripping and rotating the tubular 125 (Figure 2c). The pistons 117, 118 and cylinders 119, 120 are now actuated. The pins 115 follow slot 116 and the clamp 102 moves upwardly, lifting the tubular 125 over the tool 127 (Figure 2d). The tool 127 can now be actuated to grip the tubular 125.

At this stage the elevator 102 is released and the top drive 105 lowered to enable the tubular 125 to be connected to the string of tubulars in the slips and torqued appropriately by the top drive 105.

The pistons 117, 118 and cylinders 119, 120 are meantime extended so that after the tubular 125 has been connected the top drive 105 can be raised until the elevator 102

5

10

15

20

25

30

35

40

45

50

55

is immediately below the box. The elevator 102 is then actuated to grip the tubular 125 firmly. The top drive 105 is then raised to lift the tubular string sufficiently to enable the wedges in the slips to be withdrawn. The top drive 105 is then lower to the drilling platform, the slips applied, the elevator 102 raised for the tubular 125 and the process repeated.

SUBSTITUTE SHEET (RULE 26)

Claims

5

10

15

20

25

30

35

40

45

50

55

CLAIMS

1. An apparatus for facilitating the connection of tubulars using a top drive and comprising a winch (15), at least one wire (4, 5), and a device (2) for gripping a tubular (3), the arrangement being such that, in use, the winch (15) can be used to winch said at least one wire (4, 5) and said device (2) to position a tubular (3) below said top drive.

2. An apparatus as claimed in Claim 1, further comprising a suspension unit (9) for coupling the tubular to the top drive.

3. An apparatus as claimed in Claim 2, wherein said suspension unit (9) has a static part fixed with respect to a top drive and a dynamic part movable relative thereto.

4. An apparatus as claimed in Claim 3, wherein said winch (15) is located on said static part of said suspension unit (9).

5. An apparatus as claimed in Claim 4, comprising a guide (7) located on said dynamic part (8) of said suspension unit (9).

6. An apparatus as claimed in Claim 5, comprising a pulley wheel (11) on said static part of said suspension unit (9).

7. A method of facilitating the connection of tubulars using a top drive and comprising the steps of attaching at least one wire to a tubular, the wire depending from

the top drive or from a component attached thereto, and winching the wire and the tubular upwards to a position beneath the top drive.

8. An apparatus for facilitating the connection of tubulars using a top drive, said apparatus comprising an elevator (102) and a pair of bails (103, 104), characterised in that said elevator (102) is, in use, movable relative to said pair of bails (103, 104).

9. An apparatus as claimed in Claim 8, wherein, in use, said elevator (102) is movable along said pair of bails (103, 104).

10. An apparatus as claimed in Claim 8 or 9, further comprising a piston (117, 118) and cylinder (119, 120) operatively connected between said pair of bails (103, 104) and said elevator (102).

11. An apparatus as claimed in Claim 10, wherein said piston (117, 118) and cylinder (119, 120) are pneumatically or hydraulically operable.

12. An apparatus as claimed in any of Claims 8 to 11, wherein said pair of bails (103, 104) comprise slots (116, 116a) in which pins (115) of said elevator (102) are arranged.

13. An apparatus as claimed in any of Claims 8 to 12, wherein said pair of bails (103, 104) are attached to a top drive on an axle (106) and are movable thereabout.

5

10

14. An apparatus as claimed in Claim 13, further comprising at least one piston and cylinder (108, 109) for moving said pair of bails (103, 104) and said axle (106).

15

15. A method for facilitating the connection of tubulars using a top drive, said method comprising the step of using an elevator to move a tubular to a position below said top drive, wherein the elevator depends from the top drive or from a component attached thereto.

20

25

16. A method according to Claim 15, wherein the elevator is connected to the top drive or to said component by way of a pair of bails, the method comprising the step of using said elevator to move said tubular in relation to said pair of bails towards or away from a tool for gripping said tubular.

30

35

40


45

50

55


SUBSTITUTE SHEET (RULE 26)

FIG. 1a




2/9

FIG. 1b




3/9

FIG. 1c




4/9

FIG. 1d




5/9

FIG. 1e




6/9




7/9

FIG. 2b




8/9



9/9

FIG. 2d



INTERNATIONAL SEARCH REPORT

Intern 1st Application No
PCT/GB 99/02704

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E21B19/16 E21B19/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X.	US 4 793 422 A (KRASNOV IGOR) 27 December 1988 (1988-12-27) column 2, line 20-22 figures 2-4 ---	8,15,16
A	US 3 913 687 A (GYONGYOSI LASZLO ET AL) 21 October 1975 (1975-10-21) abstract figures 1-4 ---	1,7
A	EP 0 171 144 A (WEATHERFORD US INC) 12 February 1986 (1986-02-12) figures 1-3 ---	1,7
A	US 5 251 709 A (RICHARDSON ALLAN S) 12 October 1993 (1993-10-12) column 7, line 19-24 figure 4 ---	8,15
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "A" document member of the same patent family

Date of the actual completion of the international search

19 November 1999

Date of mailing of the international search report

08/12/1999

Name and mailing address of the ISA

European Patent Office, P.O. 5018 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schouten, A

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 99/02704

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 857 450 A (GUIER W) 31 December 1974 (1974-12-31) column 7, line 1-3 figure 5A -----	8,15

1

Form PCT/ISA210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/GB 99/ 02704

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02704

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4793422 A	27-12-1988	NONE	
US 3913687 A	21-10-1975	ZA 7500473 A	28-01-1976
EP 0171144 A	12-02-1986	CA 1239634 A	26-07-1988
		JP 61038089 A	24-02-1986
		NO 176287 B	28-11-1994
US 5251709 A	12-10-1993	NONE	
US 3857450 A	31-12-1974	NONE	

